



Powered by Innovation ♦ Proven by Performance

Herculite Natura®

TYPICAL PROPERTIES REPORT

| PROPERTY | TEST METHOD | TYPICAL TEST RESULTS | |
|------------------------------|-----------------------|-----------------------------------------|---------------|
| English | | English | Metric |
| Weight, oz. per sq. yd. | ASTM D3776 Method C | 18 oz. +/- 10% | 610 g +/- 10% |
| Adhesion. (lbs./2 in.) | ASTM D751 (Free Peel) | Cannot Separate | |
| Breaking Strength (lbs./in.) | ASTM D5034 | W 250 F 185 | W 1112 F 823 |
| Tear Strength (lbs.) | ASTM D2261/1 | W 80 F 55 | W 356 F 245 |
| Hydrostatic Burst (PSI) | ASTM D751 | 370 | 2551 |
| Waterproof | | Yes | |
| Flame Resistance | ASTM 6413 | Pass Meets Calif. State Fire Marshal | |

Width: 60 inches
Roll Size: 50 Yards

The information contained in this report is believed to be reliable. It is offered in good faith and intended for use as a general guide. Herculite makes no guarantee of results and assumes no obligation or liability whatsoever in connection with the possible use of this information. This report, including any statements concerning the possible use of our products, is not a license to operate under, or intended to suggest infringement of any existing patents.

HERCULITE PRODUCTS, INC.
P.O. Box 435, Emigsville, PA 17318
(800) 772-0036 (717) 764-1192
FAX: (717) 764-5211
www.herculite.com customercare@herculite.com