Polytex®+ / Comtex®+ / Architec 400®

POLYFAB™




Polytex®+

Roll Width: 150 inches • Weight: 7oz/yard² • Put Up: 33 yards, center folded


Polytex®+ is made of High-Density Polyethylene (HDPE) fire retardant shade fabric, manufactured with monofilament and tape yarns. New and improved pigmentation allows for extended color life. Polytex+ is heat-set reducing curling and shrinkage offering improved dimensional stability. Designed for architectural shade sails and outdoor shade structures like canopies and patio shade sails where sun protection is needed. It offers a high-strength-to-weight ratio, mildew resistance, and 12-year warranty against UV degradation. This lightweight shade cloth is lead and phthalate free.


FR Standards Met: NFPA 701 TM 2

Colors are representative only. Small variations in shade should be anticipated and are with commercial tolerances.



















Paperbark 865168


Cappuccino 865189


Sandstone 865167


Orange 865290















Lemon 865197


Grape 865195


Red 865187

Manor Red 865188

Bronze 865179

















Sage 865171

Midnight Green 865161

Navy Blue 865165

Cafe Noir 865191

Black 865181




865185




Woodland Grey

865174



865176



Slate Gray 865173



Comtex®+

Roll Width: 150 inches • Weight: 10oz/yard² • Put Up: 33 yards, center folded


Comtex®+ is a knitted High-Density Polyethylene (HDPE) fire retardant shade fabric. Comtex+ is heat-set allowing for less curling and shrinkage, offering improved dimensional stability. Designed for medium-to-large architectural shade sails, tension membrane structures and commercial shade structures. This versatile fabric performs excellency for both commercial and residential applications. New and improved pigmentation allows for extended color life. It delivers lasting protection from the sun's rays with a 12-year warranty against UV degradation. This shade cloth is lead and phthalate free.

FR Standards Met: NFPA 701 TM 2


Colors are representative only. Small variations in shade should be anticipated and are with commercial tolerances.




White 865283




Porcelain 865265




Paperbark 865285




Sandstone 865257




Cappuccino 865279




Aquamarine 865253



Sage 865261




Lemon 865287



Rust 865259



Red 865277




Silver 865275




Smoke 865289




Monument 865288



Slate Gray 865263



Midnight Green 865251



Navy Blue 865255



Black 865271



Architec 400®

Roll Width: 150 inches • Weight: 12 oz/yard²
Put Up: 55 yards, not folded


Architec 400° is a high-strength, UV-stabilized knitted shade cloth. It is designed for large, commercial tension structures and shade sails. This High-Density Polyethylene (HDPE) shade fabric incorporates the latest in ultraviolet stabilizers that provide color consistency and colorfastness. Architec 400 has a 15-year warranty against UV degradation and is lead and phthalate free.

FR Standards Met: ASTM E-84 Class 1 or A rating


Colors are representative only. Small variations in shade should be anticipated and are with commercial tolerances.




Porcelain 865150




Cappuccino 865143




Lemon 865145



Lime 865146




Orange 865149




Midnight Green 865147




Navy Blue 865148



Turquoise 865153



Aquamarine 865140



Grape 865144



Black 865142



Slate Gray 865151



	Polytex®+	Comtex®+	Architec 400°
COLORS	SHA	DE FACTO	R %
Aquamarine	91	85	91
Black	97	95	97
Bronze	87	-	-
Café Noir	96	-	-
Cappuccino	87	90	87
Lemon	72	75	69
Grape	79	-	78
Lime	79	-	88
Midnight Green	91	94	93
Navy Blue	93	96	92
Orange	84	-	85
Porcelain	74	80	73
Red	88	90	-
Rust	-	87	-
Sage	92	93	-
Sandstone	88	88	-
Silver	88	94	-
Slate Gray	94	97	95
Turquoise	-	-	85
White	76	77	-
Paperbark	82	83	-
Monument	96	94	-
Smoke	-	90	-
Woodland Grey	91	-	-
Manor Red	93	-	-

Polytex®+

FIRE STANDARD COMPLIANCE	NFPA 701 TM 2 (2019), ASTM E-84 (CLASS 1 OR A RATING)		
Technical Specifications	Units	Warp	Weft
Breaking Force (ASTM D-5034)	lbs	120	296
Elongation at Break (ASTM D-5034)	%	75	61
Tearing Strength (ASTM D-2261)	lbs	17	25
Mullen Burst (ASTM D-3786)	lbs/in	Face	444
Ball Burst (ASTM D-3787)	lbf	Face	293

Comtex®+

FIRE STANDARD COMPLIANCE	(CLASS 1 OR A RATING)			
Technical Specifications	Units	Warp	ļ	Weft
Breaking Force (ASTM D-5034)	lbs		268	340
Elongation at Break (ASTM D-5034)	%		110	75
Tearing Strength (ASTM D-2261)	lbs		31	34
Mullen Burst (ASTM D-3786)	lbs/in	ı	Face	548
Ball Burst (ASTM D-3787)	lbf	ı	Face	418

Architec 400®

Mullen Burst (ASTM D-3786)

Ball Burst (ASTM D-3787)

Technical Specifications	Units	Warp	Ţ	Weft
Breaking Force (ASTM D-5034)	lbs		342	270
Elongation at Break (ASTM D-5034)	%		87	96
Tearing Strength (ASTM D-2261)	lbs		41	38

lbs/in

lbf

FIRE STANDARD COMPLIANCE ASTM E-84 (CLASS 1 OR A RATING)



Need help?
Your customer care team is just a call or click away.

800.786.1876 | trivantage.com

593

450+

Face

Face