







Due to the technical limitations of digital cameras and inconsistencies of display monitors, the characteristics and colors of the fabrics seen on your screen may be slightly different than the actual product.

T18FVS026 Flat Black

TEXTILENE® nano™ 95 is a durable, yet lightweight synthetic fabric. It is lighter and finer with the same technical qualities as the original TEXTILENE®. TEXTILENE® nano™95 is excellent for exterior and interior use and can reduce energy costs while blocking up to 95% of the sun's harmful rays.

*Custom colors and widths available. Minimum order of 1000 yds. Upcharges may apply. ** Available in 33.3 lyd rolls.

Specifications

REACH Compliant - Regulated by Registration, Evaluation, Authorization and Restriction of Chemicals. REACH places greater responsibility on industry to manage the risks that chemicals may pose to human health and the environment.





Children's Toy Act - Does not contain harmful phthalates listed under Section 108 of the Consumer Product Safety Improvement Act of 2008 (CPSIA).

Fire Classification - Passes California U.S. Title 19 (small scale), NFPA701-2015 TM#1 (small scale), NFPA 101 (Class A Rating), UBC (Class 1), BS 5867 2008 Part 2 Type B Performance, NFPA 701 TM #2 (large scale), and CAN/ULC-S 109-03 (large and small scale)





Environmental Certification - GREENGUARD gold certified. Acceptable for use in environments such as schools and healthcare facilities. Complies with requirements of the State of California's Department of Public Health "Standard Method for Testing and Evaluation of Volatile Organic Chemical Emissions from Indoor Sources Using Environmental Chambers, Version 1.1 (2010)" (also known as California Section 01350).



RoHS Compliant - Free of Lead (Pb), Cadmium (Cd), Mercury (Hg), Hexavalent chromium (Hex-Cr), Polybrominated biphenyls (PBB), and Polybrominated diphenyl ethers (PBDE).





Bacteria and Fungal Resistance - Passes ASTM E 2180, ASTM G21. Includes specially formulated antimicrobial.

Technical Data

Item Number: T18FVS, T18FVT

Product Description: A woven fabric using .014" diameter vinyl coated 420 denier polyester core yarns woven in the warp and fill.

Attribute	ASTM	Warp	Fill	Typical
Construction, end/inch	D3775-17	36.0 ±0.5	34.0 ±0.5	
Weight, oz/yd ²	D3776-09			14.7
Weight, g/m ²	D3776-09			498.5
Tensile Strength (grab), lbf / daN	D5034-09	423.6/ 192.1	382.2/ 173.4	
Tensile Strength (strip), lbf / daN	D5035-11	218.5 / 99.1	188.4 / 85.5	
Tear Strength (trapezoidal), lbf / daN	D1117-99	58.4 / 26.5	42.2 / 19.1	
Elongation, %	D5035-11	12.7	11.6	
Abrasion Resistance CS10/500 cycles/ with no added weight)	D3884-09		No Exposure of Core Yar	n
Flammability Rating			CA Title 19 & NFPA 701	
Weatherability, 1200 hours	G154-16		No Discoloration	
Mildew Resistance	G21-13		Pass	
Thickness, inches/mm	D1777-15			0.026 / 0.66

Fenestration Properties for Twitchell Shade Material Exterior Use

45 Degree Profile Angle

 Total Solar
 Visible
 Insulating Glass

 Description
 Ts
 Rs
 As
 Tv
 Rv
 Av
 1/2" Clr.
 1" Clr.
 1" HA

 Black
 5
 8
 87
 6
 9
 85
 0.11
 0.11
 0.11

DISTRIBUTED OR MANUFACTURED BY:









Due to the technical limitations of digital cameras and inconsistencies of display monitors, the characteristics and colors of the fabrics seen on your screen may be slightly different than the actual product.

T18FVS026 Flat Black