

CLEARCO 444 ADHESIVE SPRAY



Product Information

#1 Foam-to-Foam Adhesive Spray on the Market



Net Wt. 12 oz. (340 grams)

Clearco 444 Adhesive is a clear spray that provides either permanent or pressure sensitive adhesion. Its **Web Pattern is ideal for porous and rough surfaces**. Apply to one side for pressure sensitive tack, or to both sides for permanent bond. Clearco 444 Does Not contain Chlorinated Solvents or Ozone Depleting Chemicals; it meets California VOC requirements, 2002, the strictest environmental requirements in the United States

FEATURES

- | | |
|---|--|
| <ul style="list-style-type: none">• Best Foam to Foam Adhesive on the Market• Pressure Sensitive Adhesive• Non-Clogging Nozzle• Seamless Bond-Line | <ul style="list-style-type: none">• 2002 California VOC Compliant• No CFC's• Clear, Uniform Spray Pattern• Quick Drying |
|---|--|

APPLICATIONS

Foam To Foam

To Bond Foam to Foam, spray both sides of Foam. Clearco 444 becomes Tacky in Seconds, and pieces can be joined almost immediately. This provides a Permanent Bond that is ideal for building layers of foam or to attach edges together for continuous feed.



Formulated for Foam-to-Foam & Foam-to-Fabric applications.

Foam To Fabric:

For quick pressure sensitive bond, spray foam and lay material on top. This holds material in place and prevents shifting. Clearco 444 is a high solids adhesive that **has Low Soak-in and Will Not Bleed through the Material**.

For Information or Sample Requests, Contact:

3430 G. Progress Drive

Bensalem, PA 19020

Tel: 800 533-5823

Fax: 215 639-2919

Email: info@clearcoproducts.com

Web: www.clearcoproducts.com

INDUSTRIES FOR CLEARCO 444 APPLICATIONS

- | | |
|---|--|
| <ul style="list-style-type: none">• FURNITURE• MATTRESS MANUFACTURES | <ul style="list-style-type: none">• GARMENT & EMBROIDERY• SCREEN PRINTERS |
|---|--|

SPECIFICATIONS		
Appearance	Whitish Color	
Can Size	20 oz. (17.5 fl. oz.)	
Net Wt.	12 oz.	
Packing	12-12 oz. net wt. cans per Case	
Spray Pattern	Web	
Bond	Permanent/Temporary	
CAS Information	Acetone	CAS-67-64-1
	Hexane	CAS-110-54-3
	Isobutane/Propane Blend	CAS-74-98-6

SPRAYING

Shake can before use. After use, invert the can and short burst to clear nozzle.

CONTAINS

Isobutane CAS-75-28-5, Propane CAS-74-98-6, Hexane CAS-110-54-3, Acetone CAS-67-64-1, Glycerin Ester or Resin CAS-25038-32-8.

CAUTION

CONTENTS ARE EXTREMELY FLAMMABLE AND UNDER PRESSURE. Store below 120 degrees F, away from heat sources and out of direct sunlight. Do not puncture or incinerate (burn). Use in well ventilated areas. Harmful or fatal if swallowed. Never use direct heat to warm aerosol cans! Only warm water. Read Material Safety Data Sheet for more hazardous information.

FIRST AID

If swallowed, **DO NOT** induce vomiting. Contact physician immediately. In case of eye contact, flush immediately with clear water for a minimum of 15 minutes and seek medical attention. For skin contact, wash with soap and water. If overcome by vapors, remove to fresh air.

KEEP AWAY FROM CHILDREN

OTHER CLEARCO PRODUCTS TO CONSIDER

- Clearco 900 Adhesive Spray
- Mist 600 Adhesive Spray
- Clearco 877 Adhesive Spray
- Cold Galvanizing Spray
- Zinc Rich Primer (1 to 5 gal containers)
- Silver Zinc Primer (1 to 5 gal containers)
- Blue Coat 5000 Anti-Spatter (bulk)
- Aqua 2000 Anti-Spatter (aerosol)
- Cold Shield Heat Shield
- Mr. Clearco Silicone Spray
- Mr. Clearco Glass Glass Cleaner

CLEARCO

**3430 G PROGRESS DRIVE
BENSALEM, PA 19020
Tel: (800) 533-5823
Fax: (215) 639-2919**